

REXOIL

TRANSMISSION

80W GL-5

REXOIL TRANSMISSION 80W is special gear oil which is formulated with superior additives and mineral base oils derived from modern refining. It's manual transmission fluid for mechanical gearboxes and axles in cars and trucks as well as construction and agricultural machinery.

Properties

0.

- Have ideal shear-stable formulation give improved flow properties and shiftability at low temperatures.
- Provides increased protection and lubrication of the gearbox and the transaxle over a wide temperature range.
- Have extreme pressure (EP) resistant to corrosion and oxidation and antifoaming properties.

Approvals and Specifications

- API GL-5/GL-4
- MAN 342M-1, MAN 342 M-2
- ZF TE-ML 05A, 7A, 12E, 16B, C and D, 17B, 19B, 21B

0

Scania STO 1:0

• Volvo 1273.12

• DIN 51517 Part 3

• U.S. Steel 224

• AGMA 9005-D94

Technical Properties

| Test | Method | Typical Properties |
|------------------------------------|------------|--------------------|
| Kinematic Viscosity (100°C), [cSt] | ASTM D445 | Min. 7,0 |
| Viscosity Index | ASTM D2270 | Min. 95 |
| Flash Point, °C | ASTM D92 | Min. 190 |
| Pour Point, °C | ASTM D97 | Max33 |

0

REKSOIL PETROKİMYA SAN. VE TİC. A.Ş.

Adres: Birlik Organize Sanayi Bölgesi Doğu Cd. No:19-21 Tuzla – ISTANBUL - TÜRKİYE Tel: +90 216 593 35 70 Fax: +90 216 593 35 78 www.rexoil.com.tr